

**WOOD &  
RESILIENT**

**WATERBORNE**



# Bona SuperSport Line Paint

**BONA SUPERSPORT SYSTEM** – GREAT SURFACES FOR GREAT GAMES



## Bona SuperSport Line Paint

Great surfaces for great games

Specialist two-component line-marking paint for use on indoor sport floors. Developed for use with the Bona SuperSport System for both wood and resilient flooring. Available in 10 vibrant colours.

### COLOUR VERSIONS



BLACK  
RAL: 9005



DARK BLUE  
RAL: 5010



LIGHT BLUE  
RAL: 5012



DARK GREEN  
RAL: 6029



LIGHT GREEN  
RAL: 6018



RED  
RAL: 3000



ORANGE  
RAL: 2004



VIOLET  
RAL: 4008



YELLOW  
RAL: 1021



WHITE  
RAL: 9016

### APPLICATION

Add hardener to paint and immediately stir the mixture until homogenous. Use within 3 hours. Apply paint using a fine brush or roller. Avoid accumulations of paint and overlap wet-on-wet without interruptions. Note that poor coverage affects the hiding ability. Remove the masking tape directly or after the paint has dried thoroughly. Avoid pulling the tape when the paint is semi-dry. Let it dry completely. If necessary, make a second application of paint. Protect the painted areas with 1-2 layers of Bona SuperSport/SuperSport HD. If the paint has dried for more than 12 hours then lightly sand the paint with a Bona Scrad Pad prior to overcoating.

### KEY BENEFITS

- 2 hours drying time
- 50% faster to start applying coat
- Superb hiding ability
- Low odour

### TECHNICAL DATA

<b>Type of paint:</b>	Waterborne 1-component polyurethane dispersion
<b>Drying time:</b>	Line-markings: 1-2 hours at 20°C/60° R.H.
<b>Pot life:</b>	max 3 hours at 20°C
<b>Application tools:</b>	Fine bristle brush or small, fine roller
<b>Application rate:</b>	6-10 m <sup>2</sup> /litre (167-100g/ m <sup>2</sup> ) per coat = 120-200 meters 50 mm wide line
<b>Safety:</b>	Paint: Unclassified Hardener: Classified, see Safety Data Sheet for more information
<b>Cleaning:</b>	Wipe tools free from residual material before cleaning with a minimal amount of water. Dried material can be removed with acetone.
<b>Shelf life:</b>	2 years from date of production in unopened original container
<b>Storage/transport:</b>	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
<b>Disposal:</b>	Wastes and emptied containers should be handled in accordance with local regulations.
<b>Pack sizes:</b>	1 x 1 litre